


EDMONSTON STORMWATER PUMPING STATION
 LIMIT OF PAVING (MATCH EX. ASPHALT JOINT)
 PERFORM ASPHALT FULL DEPTH PATCH

APPROXIMATE SELECTED QUANTITIES ON THIS SHEET		
DESCRIPTION	UNITS	QTY
MILL EXIST PAVEMENT 2 INCH	SY	258
2 INCH HMA SURFACE 9.5MM PG 64-22	TON	31
6 INCH HMA BASE 19.0MM PG 64-22	TON	73
6 INCH GRADED AGGREGATE SUBBASE (GASB) COURSE	SY	205
REMOVE SIDEWALK	CY	2
CONCRETE SIDEWALK RAMP TYPE "A"	EA	3
CONCRETE SIDEWALK RAMP TYPE "B"	EA	1
MODIFIED CONCRETE CURB	LF	15
CONCRETE CURB AND GUTTER (PRINCE GEORGE'S COUNTY STD. NO. 300.01)	LF	111
THERMOPLASTIC CROSSWALK, 12 INCH	LF	260
THERMOPLASTIC STOP BAR, 24 INCH	LF	23
TURFGRASS ESTABLISHMENT	SY	46
TOPSOILING - 2 INCH	SY	46
RELOCATE EX. GROUND MOUNTED SIGNS AND SUPPORT	EA	3
RELOCATE EX. GROUND MOUNTED TRASH AND COVER	EA	1
4 FOOT HIGH GALVANIZED LINK FENCE AND POSTS	LF	20
REMOVE AND DISPOSE OF EXISTING FENCE	LF	20
REMOVE OLD & INSTALL NEW C.L.F.	LF	20
ALL WAY SIGN 18" x 6" R1-1	EA	1
CLASS 2 EXCAVATION	CY	72
4 INCH GRADED AGGREGATE SUBBASE (GASB) COURSE	SY	37
DETECTABLE WARNING SURFACE FOR CURB RAMPS	SF	60

- LEGEND**
- (A) THERMOPLASTIC STOP BAR, 24 INCH
SEE DWG. DE-01
 - (B) THERMOPLASTIC CROSSWALK, 24 INCH
SEE DWG. DE-01 (PAID UNDER THE PAY ITEM FOR "THERMOPLASTIC CROSSWALK, 12 INCH")
 - (C) CONCRETE SIDEWALK RAMP TYPE "A" PER PRINCE GEORGE'S COUNTY STD. NO. 300.07 WITH 2' SIDE FLARES.
 - (D) CONCRETE SIDEWALK RAMP TYPE "A" PER PRINCE GEORGE'S COUNTY STD. NO. 300.07 WITH MODIFIED CONCRETE CURB PER PRINCE GEORGE'S STANDARD NO. 300.01.
 - (E) CONCRETE SIDEWALK RAMP TYPE "B" PER PRINCE GEORGE'S COUNTY STD. NO. 300.08
 - (F) REMOVE EXISTING CHAIN LINK FENCE AND INSTALL NEW CHAIN LINK FENCE PER PRINCE GEORGE'S COUNTY STD. NO. 300.26
- APPROXIMATE RIGHT OF WAY BASED ON GEOGRAPHIC INFORMATION SYSTEM FROM PRINCE GEORGE'S COUNTY

- NEW CONCRETE SIDEWALK
- SIDEWALK REMOVAL
- DETECTABLE WARNING SURFACE
- NEW CURB AND GUTTER
- FULL DEPTH PATCH
- MILL & RESURFACING

- NOTES:**
- THESE PLANS ARE NOT BASED ON FIELD RUN SURVEY. LOCATION OF EXISTING AND PROPOSED FEATURES SHOWN ON PLANS ARE APPROXIMATE.
 - SAW CUTTING FOR NEW PAVING AND CURB, SHALL BE INCIDENTAL TO THE ASPHALT PAVING ITEMS.
 - EX. SIGNS LOCATED AT THE SIDEWALK RAMP CONSTRUCTION, SHALL BE RELOCATED AT A MINIMUM OF 24 INCHES FROM THE FACE OF CURB TO THE EDGE OF SIGN FACE, OR 1' MIN. FROM THE BACK OF PROP. SIDEWALK TO THE EDGE OF SIGN FACE.
 - ALL DIMENSIONS FROM THE CROSSWALK ARE MEASURED TO THE FACE OF CURB OF THE INTERSECTING STREET.



MATCH LINE - SEE SHEET PS-04

PENNONI ASSOCIATES INC.
 351 W Camden Street, Suite 200
 Baltimore, MD 21201
 T 410.878.9550
 F 410.878.9551

PROFESSIONAL CERTIFICATION

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.
 LICENSE NO.: 33919
 EXPIRATION DATE: 01/25/2025

DATE	NO.	REVISIONS	BY
04/26/23	1	ADDENDUM NO. 1	DK
05/04/23	2	ADDENDUM NO. 2	DK

RIVERDALE PARK ROAD IMPROVEMENT PROGRAM - FY2023

TOWN OF RIVERDALE PARK
 PRINCE GEORGE'S COUNTY, MD

50TH AVE AT TAYLOR RD

5008 QUEENSBURY ROAD
 RIVERDALE PARK, MD 20737
 DEPARTMENT OF PUBLIC WORKS

CONTRACT NO. DWP 2023-003
 DATE 04/13/2023
 DRAWING SCALE 1" = 40'
 DRAWN BY DK
 APPROVED BY AM / EH
 DWG. NO. PS-04 OF 34

ROADWAY PLAN

SHEET 10 OF 40

